




HYDRA

DESCRIPTION: Paver **TEXTURE:** Smooth

Pallet Overview



Specifications per pallet



96 units / pallet

	Imperial	Metric
Product dimension (L x W x H)	11 ¹³ / ₁₆ x 7 ⁷ / ₈ x 3 ¹⁵ / ₁₆	300 x 200 x 100
Cubing	62 ft ²	5.76 m ²
Approx. Weight	2 811 lbs	1 275 kg
Number of rows	8	
Coverage per row	7.75 ft ²	0.72 m ²
Lin. coverage per row	11.80 lin. ft	3.60 lin. m



Smooth
Chestnut Brown


Smooth
Grey

Smooth
Shale Grey

Smooth
Onyx Black

Laying Patterns Options

01 | Linear



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

NOTES

See page 6 for icons description.

See page 19 for more information about applications.

See page 20 and 97 for more technical information.

JOINT WIDTH: ½" (13 mm)

% OF SURFACE OPENING: 8.3 %

INFILTRATION RATE: 605 in./hr (15 345 mm/hr)

CHARACTERISTICS

- Clamp or Mechanical tool available for machine installation. Check with your local Techo-Bloc representative for more information.
- 6000 to 8000 sq. ft can be installed per day with mechanical installation and a team of 5 persons
- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.