



CUT STONE

FOSSIL SPIRE
CUT STONE

GEOLOGY

limestone - quarried in USA

COLOR RANGE

yellows & creams to slight buffs, mocha & cool grays, mottled with occasional fossils; swirls are common

CONSISTENCY BLOCK/SLAB

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 165 =$
approx 155 pounds per cubic foot

ASTM TESTING DATA

FOSSIL SPIRE C97

water absorption—0.45%

density—165.33 pcf

FOSSIL SPIRE C99

modulus of rupture

perpendicular—1980 psi

parallel—2420 psi

FOSSIL SPIRE C170

compressive strength—13,990 psi

PANEL INSTALLATION SHOWN


Mortar: Western Type S

Joint Type: Struck

Size - 4" x 24" thermalled finish



THERMALLED



ARCHITECT/DESIGNER INFO

BIM DETAILS - SCAN
Revit, Hatch Patterns,
Seamless Textures,
3-Part Specs, DWGS,
SDS, Warranty



CUT STONE FOSSIL SPIRE CUTSTONE


BRUSHED




BUSHHAMMERED




BURNISHED



VELOUR



SANDED



SANDBLASTED



www.buechelstone.com